



LOW PROFILE SERIES FORKLIFT

Technical Specifications

Mast Type	Fixed Mast
Capacity	4,000
Diesel Engine	25 HP
Engine Emission	Tier 4
Max RPM	2750
Electrical System	12 Volt
Drive Tires	27"
Steering	23"
Hydraulic Cylinder	Steer Cylinder
Max Speed	15 MPH
Max Grad-ability	32%
Ready to Operate Weight	4300
Mast Tilt	8 degrees/7 degrees
Side Shift	4"
Forks	48"
Scissor Reach	44"
Height to Top of Canopy	87"
Load Spacing-Frame	59" (option 53,59,64,68)
Overall Width	86"
Overhang	58"
Lift Height	67" Two Stage
Mast Raised Height	123"
Mast Height Collapsed	78.75"
Ground Clearance	6"



**The only truck-mounted
Single Axle Solution®**



**The longest standard
reach in the industry**



**The lightest, fastest,
most versatile forklift in
the industry**



**Centralized weight
distribution**



**Lowest ground pressure
(LGP) of any forklift on
the market**

Donkey Forklifts

2730A Highway 15
Bay Springs, MS 39422
800-383-3018



MADE IN THE USA

CHECK OUT THE REST OF OUR PRODUCTS AT
WWW.DONKEYFORKLIFT.COM